

MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.
430 S. WHEELING ROAD
WHEELING, IL 60090

PRODUCT NAME: BULK CUTTING OIL – NO TRICHLOROETHYLENE

EMERGENCY TELEPHONE: 800-535-5053
INFORMATION TELEPHONE: 847-541-7220
FAX NUMBER: 847-541-7986
PREPARED BY: JIM ARMSTRONG

REVISION DATE: SEPT. 1, 2009
PRODUCT NUMBER: 413 Bulk - NT
D.U.N.S. NUMBER: 00-299-4168

THIS MSDS IS APPLICABLE TO: 41301B, 41305B and 41355B UNITS

SECTION I. IDENTIFICATION

CHEMICAL NAME: LUBRICANT OIL
CHEMICAL FAMILY: SULPHURIZED ALIPHATIC OIL
FORMULA: 41301BNT, 41305B
SYNONYMS: SLIDE CUTTING OIL
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE
H.M.I.S. RATING: 2, 2, 0, G
1 & 5 GALLON SHIPPING INFORMATION:
DOT HAZARD CLASSIFICATION: ORM-D
DOT SHIPPING NAME: CONSUMER COMMODITY
IDENTIFICATION NUMBER: NONE
PACKING GROUP: N/A

SECTION II. PHYSICAL DATA

BOILING POINT: 200-450 DEGREES F.
FREEZING POINT: 0 DEGREES F.
SPECIFIC GRAVITY (H₂O = 1): .9
WEIGHT PER GALLON @ 60 F.: 7.56
VAPOR PRESSURE @ 70 F. (MM HG): 59
VAPOR DENSITY (AIR = 1): >1
SOLUBILITY IN WATER, % BY WEIGHT: NIL
PERCENT VOLATILE BY WEIGHT: 100
EVAPORATION RATE (MINUTES): DOES NOT EVAPORATE
APPEARANCE AND ODOR: BROWN VICIOUS OIL – CHLORINATED SOLVENT ODOR

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL:	APPROX. WT. %:	CAS NUMBER:	PEL(OSHA):
LUBRICANT OIL	100	MIXTURE	N/A

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: N/A UEL: N/A (VOLUME %)
FLASH POINT: 315 DEGREES F.
EXTINGUISHING MEDIA: CO₂, FOAM, DRY CHEMICAL, WATER FOG
SPECIAL FIRE FIGHTING PROCEDURES: USE SELF-CONTAINED BREATHING APPARATUS
UNUSUAL FIRE & EXPLOSION HAZARDS: MATERIAL IS COMBUSTIBLE

SECTION V. REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS
HAZARDOUS COMBUSTION BY-PRODUCTS: CO, CO₂, SO₂
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: STRONG OXIDIZERS

SECTION VI. HEALTH HAZARD DATE (ALSO SEE SECTIONS X & XI)

THRESHOLD LIMIT VALUE: N/A

- **EFFECTS OF OVEREXPOSURE ***

INGESTION (SWALLOWING): NAUSEA, VOMITING
INHALATION: RESP. IRRITATION, DIZZINESS, NAUSEA
SKIN CONTACT: MAY DEFAT SKIN ON PROLONGED CONTACT
EYE CONTACT: SLIGHT IRRITATION

- **EMERGENCY AND FIRST AID PROCEDURES ***

INGESTION: DO NOT INDUCE VOMITING. GIVE VEGETABLE OIL, CALL PHYSICIAN
SKIN: WASH WITH SOAP AND WATER. APPLY HANDCREAM. LAUNDRER CONTAMINATED CLOTHING.
INHALATION: REMOVE TO FRESH-AIR LOCATION AWAY FROM EXPOSURE
EYES: RINSE WITH PLENTY COOL CLEAN WATER UNTIL IRRITATION SUBSIDES

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: ABSORB ON FIRE-RETARDANT
SAWDUST OR CLAY-DISPOSE AT APPROPRIATE WASTE DISPOSAL FACILITY IN ACCORDANCE WITH
WASTE DISPOSAL METHOD: SUPERVISED INCINERATION IN COMPLIANCE WITH APPLICABLE LAWS
AND REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION
VENTILATION: SUGGESTED
PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED
EYE PROTECTION: PROPER EYE CARE IS NEEDED IN ALL INDUSTRIAL OPERATIONS
OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: DO NOT ALLOW TO FREEZE. STORE IN
LOCATION AWAY FROM HEAT SOURCES. DO NOT EAT, DRINK, OR SMOKE IN WORK AREA.
OTHER PRECAUTIONS: DO NOT CUT, PUNCTURE, OR WELD ON OR NEAR EMPTY CONTAINERS.

SECTION X. EFFECTS OF PROLONGED EXPOSURE

NONE KNOWN

SECTION XI. CARCINOGENIC HAZARD

CALIFORNIA PROPOSITION 65: NONE
NO CARCINOGENIC HAZARDS KNOWN

SECTION XII. – SARA TITLE III REPORTING

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS REQUIRED TO BE REPORTED UNDER SARA TITLE III, SECTION 313: NONE

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.