

MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.
430 S. WHEELING ROAD
WHEELING, IL 60090

PRODUCT NAME: SLIDE SILICONE REMOVER

EMERGENCY TELEPHONE: 800-535-5053
INFORMATON TELEPHONE: 847-541-7220
FAX NUMBER: 847-541-7986
PREPARED BY: JIM ARMSTRONG

REVISION DATE: SEPT. 1, 2009
PRODUCT NUMBER: 43016
D.U.N.S. NUMBER: 00-299-4168

**** THIS MSDS PERTAINS TO BOTH 43016(PINTS) AS WELL AS 43001(05) – (GALLONS) ****

SECTION I. IDENTIFICATION

CHEMICAL NAME: NON-IONIC SURFACTANT- POLY (oxyethylene/oxypropylene) GLYCOL
CAS # 68937-66-6
CHEMICAL FAMILY: ALIPHATIC HC DERIVATIVE
FORMULA: 43016
SYNONYMS:
DOT HAZARD CLASSIFICATION: NON-HAZARDOUS LIQUID
DOT SHIPPING NAME: NONE NEEDED
CHEMICAL ABSTRACT REGISTRY NUMBER: PROPRIETARY BLEND
IDENTIFICATION NUMBER: NONE
H.M.I.S. RATING: 1,0,0,A

SECTION II. PHYSICAL DATA

BOILING POINT: NOT ESTABLISHED
FREEZING POINT: 15 DEGREES F.
SPECIFIC GRAVITY (H2O =1): 1.03
WEIGHT PER GALLON @ 60 F.: 8.59
VAPOR PRESSURE @ 70 f. (MM HG): NOT ESTABLISHED
VAPOR DENSITY (AIR = 1): PRODUCT IS NON VOLATILE
PERCENT VOLATILE BY VOLUME: 0
EVAPORATION RATE (MINUTES): N/A
APPEARANCE AND ODOR: CLEAR LIQUID, SLIGHT SURFACTANT ODOR

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL:	APPROX. VOLUME %:	TLV(UNITS):
NO KNOWN HAZARDOUS MATERIALS PRESENT		
CONTAINS NO OZONE DEPLETING CHEMICALS		

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: N/A UEL: N/A (VOLUME %)
FLASH POINT: 250 DEGREES F.
EXTINGUISHING MEDIA: A,B,C, ALL CLASS POWDER
SPECIAL FIRE FIGHTING PROCEDURES: NONE
UNUSUAL FIRE & EXPLOSION HAZARDS: NONE

SECTION V. REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS
HAZARDOUS COMBUSTION BY-PRODUCTS:
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: NONE

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: NOT ESTABLISHED

• **EFFECTS OF OVEREXPOSURE ***

INHALATION: N/A
SKIN CONTACT: MAY CAUSE IRRITATION
EYE CONTACT: TEMPORARY IRRITANT

• **EMERGENCY AND FIRST AID PROCEDURES ***

SKIN: WASH WITH SOAP AND WATER, APPLY HAND CREAM
INHALATION: N/A
EYES: WASH THOROUGHLY WITH COLD CLEAN WATER FOR 15 MINUTES
CONSULT PHYSICIAN IMMEDIATELY IF IRRITATION PERSISTS.

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: USE ABSORBENT COMPOUND TO REMOVE OR FLUSH INTO SEWER AS PERMITTED
WASTE DISPOSAL METHOD: INCINERATE OR LANDFILL AS PERMITTED BY LOCAL, STATE OR FEDERAL REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED
VENTILATION: N/A
PROTECTIVE GLOVES: MAY BE USED
EYE PROTECTION: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS.
OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS, AVOID FREEZING.
STORE AT TEMPERATURES BELOW 120° F.
OTHER PRECAUTIONS: NONE

THIS DATA IS OFFERED IN GOOD FAITH AT TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

<http://www.slideproducts.com/cleaners.htm>