



Super Grease Lubricant - Aerosol No. 43911

- New formulation contains no Chlorinated Solvents!
- Colorless
- High operating temperature range
- FDA approved and USDA Listed H1+
- Excellent dielectric
- Contains PTFE
- Compatible with other lubricants
- No silicones
- Will not wash out
- NLGI#2

Repels water. Will not separate, run, fall out. Thixotropic properties provide excellent mechanical stability when sudden temperature changes occur. Exceptional load-bearing properties. Clear, clean, non-yellowing grease. For injection molds, mold assemblies, especially medical and food grade plastic parts. Prevents corrosion.
NOTICE TO PURCHASER: User shall determine suitability of product for his intended use and assumes all risk and liability in connection herewith.

Specs

Operating Temperatures.: -45F to +650F*.

No. 43911 aerosol

Net Wt. 11 oz. (16 fl. oz.).

+ Rating applies to grease tube cartridge & 3 oz. tube.

NSF H1 rating: For use in federally inspected meat and poultry plants.

*Intermittent

Acetronic Industrial Controls Inc. 7015 Ordan Dr. Unit 6 & 7, Mississauga ON L5T 1Y2

Toll Free: 1.800.803.8871 Ph.: 905.564.7227 Fax: 905.564.6817

